

---

# Amazon Managed Blockchain

## API Reference

**API Version 2018-09-24**



## **Amazon Managed Blockchain: API Reference**

Copyright © 2023 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

## Table of Contents

Welcome .....	1
Actions .....	2
CreateAccessor .....	3
Request Syntax .....	3
URI Request Parameters .....	3
Request Body .....	3
Response Syntax .....	4
Response Elements .....	4
Errors .....	4
See Also .....	5
CreateMember .....	6
Request Syntax .....	6
URI Request Parameters .....	6
Request Body .....	6
Response Syntax .....	7
Response Elements .....	7
Errors .....	7
See Also .....	8
CreateNetwork .....	10
Request Syntax .....	10
URI Request Parameters .....	10
Request Body .....	11
Response Syntax .....	12
Response Elements .....	12
Errors .....	13
See Also .....	13
CreateNode .....	15
Request Syntax .....	15
URI Request Parameters .....	15
Request Body .....	15
Response Syntax .....	16
Response Elements .....	17
Errors .....	17
See Also .....	18
CreateProposal .....	19
Request Syntax .....	19
URI Request Parameters .....	19
Request Body .....	19
Response Syntax .....	20
Response Elements .....	21
Errors .....	21
See Also .....	22
DeleteAccessor .....	23
Request Syntax .....	23
URI Request Parameters .....	23
Request Body .....	23
Response Syntax .....	23
Response Elements .....	23
Errors .....	23
See Also .....	24
DeleteMember .....	25
Request Syntax .....	25
URI Request Parameters .....	25
Request Body .....	25

Response Syntax .....	25
Response Elements .....	25
Errors .....	25
See Also .....	26
DeleteNode .....	27
Request Syntax .....	27
URI Request Parameters .....	27
Request Body .....	27
Response Syntax .....	27
Response Elements .....	27
Errors .....	28
See Also .....	28
GetAccessor .....	29
Request Syntax .....	29
URI Request Parameters .....	29
Request Body .....	29
Response Syntax .....	29
Response Elements .....	29
Errors .....	30
See Also .....	30
GetMember .....	31
Request Syntax .....	31
URI Request Parameters .....	31
Request Body .....	31
Response Syntax .....	31
Response Elements .....	32
Errors .....	32
See Also .....	33
GetNetwork .....	34
Request Syntax .....	34
URI Request Parameters .....	34
Request Body .....	34
Response Syntax .....	34
Response Elements .....	35
Errors .....	35
See Also .....	35
GetNode .....	37
Request Syntax .....	37
URI Request Parameters .....	37
Request Body .....	37
Response Syntax .....	37
Response Elements .....	38
Errors .....	38
See Also .....	39
GetProposal .....	40
Request Syntax .....	40
URI Request Parameters .....	40
Request Body .....	40
Response Syntax .....	40
Response Elements .....	41
Errors .....	41
See Also .....	42
ListAccessors .....	43
Request Syntax .....	43
URI Request Parameters .....	43
Request Body .....	43
Response Syntax .....	43

Response Elements .....	43
Errors .....	44
See Also .....	44
ListInvitations .....	45
Request Syntax .....	45
URI Request Parameters .....	45
Request Body .....	45
Response Syntax .....	45
Response Elements .....	46
Errors .....	46
See Also .....	47
ListMembers .....	48
Request Syntax .....	48
URI Request Parameters .....	48
Request Body .....	48
Response Syntax .....	48
Response Elements .....	49
Errors .....	49
See Also .....	50
ListNetworks .....	51
Request Syntax .....	51
URI Request Parameters .....	51
Request Body .....	51
Response Syntax .....	51
Response Elements .....	52
Errors .....	52
See Also .....	53
ListNodes .....	54
Request Syntax .....	54
URI Request Parameters .....	54
Request Body .....	54
Response Syntax .....	54
Response Elements .....	55
Errors .....	55
See Also .....	56
ListProposals .....	57
Request Syntax .....	57
URI Request Parameters .....	57
Request Body .....	57
Response Syntax .....	57
Response Elements .....	58
Errors .....	58
See Also .....	58
ListProposalVotes .....	60
Request Syntax .....	60
URI Request Parameters .....	60
Request Body .....	60
Response Syntax .....	60
Response Elements .....	61
Errors .....	61
See Also .....	61
ListTagsForResource .....	63
Request Syntax .....	63
URI Request Parameters .....	63
Request Body .....	63
Response Syntax .....	63
Response Elements .....	63

Errors .....	64
See Also .....	64
RejectInvitation .....	65
Request Syntax .....	65
URI Request Parameters .....	65
Request Body .....	65
Response Syntax .....	65
Response Elements .....	65
Errors .....	65
See Also .....	66
TagResource .....	67
Request Syntax .....	67
URI Request Parameters .....	67
Request Body .....	67
Response Syntax .....	68
Response Elements .....	68
Errors .....	68
See Also .....	68
UntagResource .....	70
Request Syntax .....	70
URI Request Parameters .....	70
Request Body .....	70
Response Syntax .....	70
Response Elements .....	70
Errors .....	70
See Also .....	71
UpdateMember .....	72
Request Syntax .....	72
URI Request Parameters .....	72
Request Body .....	72
Response Syntax .....	73
Response Elements .....	73
Errors .....	73
See Also .....	73
UpdateNode .....	75
Request Syntax .....	75
URI Request Parameters .....	75
Request Body .....	75
Response Syntax .....	76
Response Elements .....	76
Errors .....	76
See Also .....	77
VoteOnProposal .....	78
Request Syntax .....	78
URI Request Parameters .....	78
Request Body .....	78
Response Syntax .....	79
Response Elements .....	79
Errors .....	79
See Also .....	79
Data Types .....	81
Accessor .....	83
Contents .....	83
See Also .....	84
AccessorSummary .....	85
Contents .....	85
See Also .....	85

ApprovalThresholdPolicy .....	87
Contents .....	87
See Also .....	87
Invitation .....	88
Contents .....	88
See Also .....	89
InviteAction .....	90
Contents .....	90
See Also .....	90
LogConfiguration .....	91
Contents .....	91
See Also .....	91
LogConfigurations .....	92
Contents .....	92
See Also .....	92
Member .....	93
Contents .....	93
See Also .....	95
MemberConfiguration .....	96
Contents .....	96
See Also .....	97
MemberFabricAttributes .....	98
Contents .....	98
See Also .....	98
MemberFabricConfiguration .....	99
Contents .....	99
See Also .....	99
MemberFabricLogPublishingConfiguration .....	100
Contents .....	100
See Also .....	100
MemberFrameworkAttributes .....	101
Contents .....	101
See Also .....	101
MemberFrameworkConfiguration .....	102
Contents .....	102
See Also .....	102
MemberLogPublishingConfiguration .....	103
Contents .....	103
See Also .....	103
MemberSummary .....	104
Contents .....	104
See Also .....	105
Network .....	106
Contents .....	106
See Also .....	108
NetworkEthereumAttributes .....	109
Contents .....	109
See Also .....	109
NetworkFabricAttributes .....	110
Contents .....	110
See Also .....	110
NetworkFabricConfiguration .....	111
Contents .....	111
See Also .....	111
NetworkFrameworkAttributes .....	112
Contents .....	112
See Also .....	112

NetworkFrameworkConfiguration .....	113
Contents .....	113
See Also .....	113
NetworkSummary .....	114
Contents .....	114
See Also .....	115
Node .....	116
Contents .....	116
See Also .....	118
NodeConfiguration .....	119
Contents .....	119
See Also .....	119
NodeEthereumAttributes .....	120
Contents .....	120
See Also .....	120
NodeFabricAttributes .....	121
Contents .....	121
See Also .....	121
NodeFabricLogPublishingConfiguration .....	122
Contents .....	122
See Also .....	122
NodeFrameworkAttributes .....	123
Contents .....	123
See Also .....	123
NodeLogPublishingConfiguration .....	124
Contents .....	124
See Also .....	124
NodeSummary .....	125
Contents .....	125
See Also .....	126
Proposal .....	127
Contents .....	127
See Also .....	129
ProposalActions .....	130
Contents .....	130
See Also .....	130
ProposalSummary .....	131
Contents .....	131
See Also .....	132
RemoveAction .....	133
Contents .....	133
See Also .....	133
VoteSummary .....	134
Contents .....	134
See Also .....	134
VotingPolicy .....	135
Contents .....	135
See Also .....	135
Common Parameters .....	136
Common Errors .....	138



# Welcome

Amazon Managed Blockchain is a fully managed service for creating and managing blockchain networks using open-source frameworks. Blockchain allows you to build applications where multiple parties can securely and transparently run transactions and share data without the need for a trusted, central authority.

Managed Blockchain supports the Hyperledger Fabric and Ethereum open-source frameworks. Because of fundamental differences between the frameworks, some API actions or data types may only apply in the context of one framework and not the other. For example, actions related to Hyperledger Fabric network members such as `CreateMember` and `DeleteMember` don't apply to Ethereum.

The description for each action indicates the framework or frameworks to which it applies. Data types and properties that apply only in the context of a particular framework are similarly indicated.

This document was last published on July 27, 2023.

# Actions

The following actions are supported:

- [CreateAccessor \(p. 3\)](#)
- [CreateMember \(p. 6\)](#)
- [CreateNetwork \(p. 10\)](#)
- [CreateNode \(p. 15\)](#)
- [CreateProposal \(p. 19\)](#)
- [DeleteAccessor \(p. 23\)](#)
- [DeleteMember \(p. 25\)](#)
- [DeleteNode \(p. 27\)](#)
- [GetAccessor \(p. 29\)](#)
- [GetMember \(p. 31\)](#)
- [GetNetwork \(p. 34\)](#)
- [GetNode \(p. 37\)](#)
- [GetProposal \(p. 40\)](#)
- [ListAccessors \(p. 43\)](#)
- [ListInvitations \(p. 45\)](#)
- [ListMembers \(p. 48\)](#)
- [ListNetworks \(p. 51\)](#)
- [ListNodes \(p. 54\)](#)
- [ListProposals \(p. 57\)](#)
- [ListProposalVotes \(p. 60\)](#)
- [ListTagsForResource \(p. 63\)](#)
- [RejectInvitation \(p. 65\)](#)
- [TagResource \(p. 67\)](#)
- [UntagResource \(p. 70\)](#)
- [UpdateMember \(p. 72\)](#)
- [UpdateNode \(p. 75\)](#)
- [VoteOnProposal \(p. 78\)](#)

# CreateAccessor

Creates a new accessor for use with Managed Blockchain Ethereum nodes. An accessor contains information required for token based access to your Ethereum nodes.

## Request Syntax

```
POST /accessors HTTP/1.1
Content-type: application/json

{
  "AccessorType": "string",
  "ClientRequestToken": "string",
  "Tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### [AccessorType \(p. 3\)](#)

The type of accessor.

**Note**

Currently, accessor type is restricted to BILLING\_TOKEN.

Type: String

Valid Values: BILLING\_TOKEN

Required: Yes

### [ClientRequestToken \(p. 3\)](#)

This is a unique, case-sensitive identifier that you provide to ensure the idempotency of the operation. An idempotent operation completes no more than once. This identifier is required only if you make a service request directly using an HTTP client. It is generated automatically if you use an AWS SDK or the AWS CLI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

### [Tags \(p. 3\)](#)

Tags to assign to the Accessor.

Each tag consists of a key and an optional value. You can specify multiple key-value pairs in a single request with an overall maximum of 50 tags allowed per resource.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AccessorId": "string",
  "BillingToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [AccessorId \(p. 4\)](#)

The unique identifier of the accessor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

### [BillingToken \(p. 4\)](#)

The billing token is a property of the Accessor. Use this token to make Ethereum API calls to your Ethereum node. The billing token is used to track your accessor object for billing Ethereum API requests made to your Ethereum nodes.

Type: String

Length Constraints: Fixed length of 42.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceAlreadyExistsException**

A resource request is issued for a resource that already exists.

HTTP Status Code: 409

### **ResourceLimitExceededException**

The maximum number of resources of that type already exist. Ensure the resources requested are within the boundaries of the service edition and your account limits.

HTTP Status Code: 429

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

### **TooManyTagsException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateMember

Creates a member within a Managed Blockchain network.

Applies only to Hyperledger Fabric.

## Request Syntax

POST /networks/*networkId*/members HTTP/1.1  
Content-type: application/json

```
{
  "ClientRequestToken": "string",
  "InvitationId": "string",
  "MemberConfiguration": {
    "Description": "string",
    "FrameworkConfiguration": {
      "Fabric": {
        "AdminPassword": "string",
        "AdminUsername": "string"
      }
    },
    "KmsKeyArn": "string",
    "LogPublishingConfiguration": {
      "Fabric": {
        "CaLogs": {
          "Cloudwatch": {
            "Enabled": boolean
          }
        }
      }
    },
    "Name": "string",
    "Tags": {
      "string" : "string"
    }
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### [networkId \(p. 6\)](#)

The unique identifier of the network in which the member is created.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### [ClientRequestToken \(p. 6\)](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the operation. An idempotent operation completes no more than one time. This identifier is required only if you make

a service request directly using an HTTP client. It is generated automatically if you use an AWS SDK or the AWS CLI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

#### [InvitationId \(p. 6\)](#)

The unique identifier of the invitation that is sent to the member to join the network.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

#### [MemberConfiguration \(p. 6\)](#)

Member configuration parameters.

Type: [MemberConfiguration \(p. 96\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "MemberId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

#### [MemberId \(p. 7\)](#)

The unique identifier of the member.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

#### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

**InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

**InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

**ResourceAlreadyExistsException**

A resource request is issued for a resource that already exists.

HTTP Status Code: 409

**ResourceLimitExceededException**

The maximum number of resources of that type already exist. Ensure the resources requested are within the boundaries of the service edition and your account limits.

HTTP Status Code: 429

**ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

**ResourceNotReadyException**

The requested resource exists but isn't in a status that can complete the operation.

HTTP Status Code: 409

**ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

**TooManyTagsException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)



- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateNetwork

Creates a new blockchain network using Amazon Managed Blockchain.

Applies only to Hyperledger Fabric.

## Request Syntax

```
POST /networks HTTP/1.1
Content-type: application/json

{
  "ClientRequestToken": "string",
  "Description": "string",
  "Framework": "string",
  "FrameworkConfiguration": {
    "Fabric": {
      "Edition": "string"
    }
  },
  "FrameworkVersion": "string",
  "MemberConfiguration": {
    "Description": "string",
    "FrameworkConfiguration": {
      "Fabric": {
        "AdminPassword": "string",
        "AdminUsername": "string"
      }
    }
  },
  "KmsKeyArn": "string",
  "LogPublishingConfiguration": {
    "Fabric": {
      "CaLogs": {
        "Cloudwatch": {
          "Enabled": boolean
        }
      }
    }
  },
  "Name": "string",
  "Tags": {
    "string" : "string"
  }
},
{
  "Name": "string",
  "Tags": {
    "string" : "string"
  }
},
{
  "VotingPolicy": {
    "ApprovalThresholdPolicy": {
      "ProposalDurationInHours": number,
      "ThresholdComparator": "string",
      "ThresholdPercentage": number
    }
  }
}
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### [ClientRequestToken \(p. 10\)](#)

This is a unique, case-sensitive identifier that you provide to ensure the idempotency of the operation. An idempotent operation completes no more than once. This identifier is required only if you make a service request directly using an HTTP client. It is generated automatically if you use an AWS SDK or the AWS CLI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

### [Description \(p. 10\)](#)

An optional description for the network.

Type: String

Length Constraints: Maximum length of 128.

Required: No

### [Framework \(p. 10\)](#)

The blockchain framework that the network uses.

Type: String

Valid Values: HYPERLEDGER\_FABRIC | ETHEREUM

Required: Yes

### [FrameworkConfiguration \(p. 10\)](#)

Configuration properties of the blockchain framework relevant to the network configuration.

Type: [NetworkFrameworkConfiguration \(p. 113\)](#) object

Required: No

### [FrameworkVersion \(p. 10\)](#)

The version of the blockchain framework that the network uses.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8.

Required: Yes

### [MemberConfiguration \(p. 10\)](#)

Configuration properties for the first member within the network.

Type: [MemberConfiguration \(p. 96\)](#) object

Required: Yes

### [Name \(p. 10\)](#)

The name of the network.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `.*\S.*`

Required: Yes

#### [Tags \(p. 10\)](#)

Tags to assign to the network.

Each tag consists of a key and an optional value. You can specify multiple key-value pairs in a single request with an overall maximum of 50 tags allowed per resource.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

#### [VotingPolicy \(p. 10\)](#)

The voting rules used by the network to determine if a proposal is approved.

Type: [VotingPolicy \(p. 135\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "MemberId": "string",
  "NetworkId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

#### [MemberId \(p. 12\)](#)

The unique identifier for the first member within the network.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

### [NetworkId \(p. 12\)](#)

The unique identifier for the network.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServiceErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceAlreadyExistsException**

A resource request is issued for a resource that already exists.

HTTP Status Code: 409

### **ResourceLimitExceededException**

The maximum number of resources of that type already exist. Ensure the resources requested are within the boundaries of the service edition and your account limits.

HTTP Status Code: 429

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

### **TooManyTagsException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateNode

Creates a node on the specified blockchain network.

Applies to Hyperledger Fabric and Ethereum.

## Request Syntax

POST /networks/*networkId*/nodes HTTP/1.1  
Content-type: application/json

```
{
  "ClientRequestToken": "string",
  "MemberId": "string",
  "NodeConfiguration": {
    "AvailabilityZone": "string",
    "InstanceType": "string",
    "LogPublishingConfiguration": {
      "Fabric": {
        "ChaincodeLogs": {
          "Cloudwatch": {
            "Enabled": boolean
          }
        },
        "PeerLogs": {
          "Cloudwatch": {
            "Enabled": boolean
          }
        }
      }
    },
    "StateDB": "string"
  },
  "Tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### networkId (p. 15)

The unique identifier of the network for the node.

Ethereum public networks have the following NetworkIds:

- n-ethereum-mainnet
- n-ethereum-goerli
- n-ethereum-rinkeby

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### [ClientRequestToken \(p. 15\)](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the operation. An idempotent operation completes no more than one time. This identifier is required only if you make a service request directly using an HTTP client. It is generated automatically if you use an AWS SDK or the AWS CLI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

### [MemberId \(p. 15\)](#)

The unique identifier of the member that owns this node.

Applies only to Hyperledger Fabric.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### [NodeConfiguration \(p. 15\)](#)

The properties of a node configuration.

Type: [NodeConfiguration \(p. 119\)](#) object

Required: Yes

### [Tags \(p. 15\)](#)

Tags to assign to the node.

Each tag consists of a key and an optional value. You can specify multiple key-value pairs in a single request with an overall maximum of 50 tags allowed per resource.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NodeId": "string"
}
```



```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NodeId \(p. 16\)](#)

The unique identifier of the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServiceErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceAlreadyExistsException**

A resource request is issued for a resource that already exists.

HTTP Status Code: 409

### **ResourceLimitExceededException**

The maximum number of resources of that type already exist. Ensure the resources requested are within the boundaries of the service edition and your account limits.

HTTP Status Code: 429

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ResourceNotReadyException**

The requested resource exists but isn't in a status that can complete the operation.

HTTP Status Code: 409

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

### **TooManyTagsException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## CreateProposal

Creates a proposal for a change to the network that other members of the network can vote on, for example, a proposal to add a new member to the network. Any member can create a proposal.

Applies only to Hyperledger Fabric.

### Request Syntax

```
POST /networks/networkId/proposals HTTP/1.1  
Content-type: application/json
```

```
{  
  "Actions": {  
    "Invitations": [  
      {  
        "Principal": "string"  
      }  
    ],  
    "Removals": [  
      {  
        "MemberId": "string"  
      }  
    ]  
  },  
  "ClientRequestToken": "string",  
  "Description": "string",  
  "MemberId": "string",  
  "Tags": {  
    "string" : "string"  
  }  
}
```

### URI Request Parameters

The request uses the following URI parameters.

#### [networkId \(p. 19\)](#)

The unique identifier of the network for which the proposal is made.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### Request Body

The request accepts the following data in JSON format.

#### [Actions \(p. 19\)](#)

The type of actions proposed, such as inviting a member or removing a member. The types of Actions in a proposal are mutually exclusive. For example, a proposal with Invitations actions cannot also contain Removals actions.

Type: [ProposalActions \(p. 130\)](#) object

Required: Yes

#### [ClientRequestToken \(p. 19\)](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the operation. An idempotent operation completes no more than one time. This identifier is required only if you make a service request directly using an HTTP client. It is generated automatically if you use an AWS SDK or the AWS CLI.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

#### [Description \(p. 19\)](#)

A description for the proposal that is visible to voting members, for example, "Proposal to add Example Corp. as member."

Type: String

Length Constraints: Maximum length of 128.

Required: No

#### [MemberId \(p. 19\)](#)

The unique identifier of the member that is creating the proposal. This identifier is especially useful for identifying the member making the proposal when multiple members exist in a single AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

#### [Tags \(p. 19\)](#)

Tags to assign to the proposal.

Each tag consists of a key and an optional value. You can specify multiple key-value pairs in a single request with an overall maximum of 50 tags allowed per resource.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "ProposalId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### ProposalId (p. 20)

The unique identifier of the proposal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ResourceNotReadyException**

The requested resource exists but isn't in a status that can complete the operation.

HTTP Status Code: 409

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

### **TooManyTagsException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteAccessor

Deletes an accessor that your AWS account owns. An accessor object is a container that has the information required for token based access to your Ethereum nodes including, the BILLING\_TOKEN. After an accessor is deleted, the status of the accessor changes from AVAILABLE to PENDING\_DELETION. An accessor in the PENDING\_DELETION state can't be used for new WebSocket requests or HTTP requests. However, WebSocket connections that were initiated while the accessor was in the AVAILABLE state remain open until they expire (up to 2 hours).

## Request Syntax

```
DELETE /accessors/AccessorId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### AccessorId (p. 23)

The unique identifier of the accessor.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DeleteMember

Deletes a member. Deleting a member removes the member and all associated resources from the network. DeleteMember can only be called for a specified MemberId if the principal performing the action is associated with the AWS account that owns the member. In all other cases, the DeleteMember action is carried out as the result of an approved proposal to remove a member. If MemberId is the last member in a network specified by the last AWS account, the network is deleted also.

Applies only to Hyperledger Fabric.

## Request Syntax

```
DELETE /networks/networkId/members/memberId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### memberId (p. 25)

The unique identifier of the member to remove.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### networkId (p. 25)

The unique identifier of the network from which the member is removed.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

**InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

**InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

**ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

**ResourceNotReadyException**

The requested resource exists but isn't in a status that can complete the operation.

HTTP Status Code: 409

**ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteNode

Deletes a node that your AWS account owns. All data on the node is lost and cannot be recovered.

Applies to Hyperledger Fabric and Ethereum.

## Request Syntax

```
DELETE /networks/networkId/nodes/nodeId?memberId=MemberId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### MemberId (p. 27)

The unique identifier of the member that owns this node.

Applies only to Hyperledger Fabric and is required for Hyperledger Fabric.

Length Constraints: Minimum length of 1. Maximum length of 32.

### networkId (p. 27)

The unique identifier of the network that the node is on.

Ethereum public networks have the following NetworkIds:

- n-ethereum-mainnet
- n-ethereum-goerli
- n-ethereum-rinkeby

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### nodeId (p. 27)

The unique identifier of the node.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ResourceNotReadyException**

The requested resource exists but isn't in a status that can complete the operation.

HTTP Status Code: 409

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetAccessor

Returns detailed information about an accessor. An accessor object is a container that has the information required for token based access to your Ethereum nodes.

## Request Syntax

```
GET /accessors/AccessorId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### AccessorId (p. 29)

The unique identifier of the accessor.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{  
  "Accessor": {  
    "Arn": "string",  
    "BillingToken": "string",  
    "CreationDate": "string",  
    "Id": "string",  
    "Status": "string",  
    "Tags": {  
      "string": "string"  
    },  
    "Type": "string"  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Accessor (p. 29)

The properties of the accessor.

Type: [Accessor \(p. 83\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServiceErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetMember

Returns detailed information about a member.

Applies only to Hyperledger Fabric.

## Request Syntax

```
GET /networks/networkId/members/memberId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### memberId (p. 31)

The unique identifier of the member.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### networkId (p. 31)

The unique identifier of the network to which the member belongs.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Member": {
    "Arn": "string",
    "CreationDate": "string",
    "Description": "string",
    "FrameworkAttributes": {
      "Fabric": {
        "AdminUsername": "string",
        "CaEndpoint": "string"
      }
    },
    "Id": "string",
    "KmsKeyArn": "string",
    "LogPublishingConfiguration": {
      "Fabric": {
        "CaLogs": {
          "Cloudwatch": {
```

```
        "Enabled": boolean
      }
    }
  },
  "Name": "string",
  "NetworkId": "string",
  "Status": "string",
  "Tags": {
    "string" : "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Member \(p. 31\)](#)

The properties of a member.

Type: [Member \(p. 93\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429



## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetNetwork

Returns detailed information about a network.

Applies to Hyperledger Fabric and Ethereum.

## Request Syntax

```
GET /networks/networkId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### networkId (p. 34)

The unique identifier of the network to get information about.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Network": {
    "Arn": "string",
    "CreationDate": "string",
    "Description": "string",
    "Framework": "string",
    "FrameworkAttributes": {
      "Ethereum": {
        "ChainId": "string"
      },
      "Fabric": {
        "Edition": "string",
        "OrderingServiceEndpoint": "string"
      }
    },
    "FrameworkVersion": "string",
    "Id": "string",
    "Name": "string",
    "Status": "string",
    "Tags": {
      "string" : "string"
    },
    "VotingPolicy": {
      "ApprovalThresholdPolicy": {
        "ProposalDurationInHours": number,

```

```
    "ThresholdComparator": "string",  
    "ThresholdPercentage": number  
  },  
  "VpcEndpointServiceName": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Network \(p. 34\)](#)

An object containing network configuration parameters.

Type: [Network \(p. 106\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServiceErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetNode

Returns detailed information about a node.

Applies to Hyperledger Fabric and Ethereum.

## Request Syntax

```
GET /networks/networkId/nodes/nodeId?memberId=MemberId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### MemberId (p. 37)

The unique identifier of the member that owns the node.

Applies only to Hyperledger Fabric and is required for Hyperledger Fabric.

Length Constraints: Minimum length of 1. Maximum length of 32.

### networkId (p. 37)

The unique identifier of the network that the node is on.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### nodeId (p. 37)

The unique identifier of the node.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Node": {
    "Arn": "string",
    "AvailabilityZone": "string",
    "CreationDate": "string",
    "FrameworkAttributes": {
      "Ethereum": {
        "HttpEndpoint": "string",
```

```
    "WebSocketEndpoint": "string"
  },
  "Fabric": {
    "PeerEndpoint": "string",
    "PeerEventEndpoint": "string"
  }
},
"Id": "string",
"InstanceType": "string",
"KmsKeyArn": "string",
"LogPublishingConfiguration": {
  "Fabric": {
    "ChaincodeLogs": {
      "Cloudwatch": {
        "Enabled": boolean
      }
    },
    "PeerLogs": {
      "Cloudwatch": {
        "Enabled": boolean
      }
    }
  }
},
"MemberId": "string",
"NetworkId": "string",
"StateDB": "string",
"Status": "string",
"Tags": {
  "string" : "string"
}
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Node \(p. 37\)](#)

Properties of the node configuration.

Type: [Node \(p. 116\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetProposal

Returns detailed information about a proposal.

Applies only to Hyperledger Fabric.

## Request Syntax

```
GET /networks/networkId/proposals/proposalId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### networkId (p. 40)

The unique identifier of the network for which the proposal is made.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### proposalId (p. 40)

The unique identifier of the proposal.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Proposal": {
    "Actions": {
      "Invitations": [
        {
          "Principal": "string"
        }
      ],
      "Removals": [
        {
          "MemberId": "string"
        }
      ]
    },
    "Arn": "string",
    "CreationDate": "string",
    "Description": "string",
  }
}
```



```
"ExpirationDate": "string",
"NetworkId": "string",
"NoVoteCount": number,
"OutstandingVoteCount": number,
"ProposalId": "string",
"ProposedByMemberId": "string",
"ProposedByMemberName": "string",
"Status": "string",
"Tags": {
  "string" : "string"
},
"YesVoteCount": number
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Proposal \(p. 40\)](#)

Information about a proposal.

Type: [Proposal \(p. 127\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListAccessors

Returns a list of the accessors and their properties. Accessor objects are containers that have the information required for token based access to your Ethereum nodes.

## Request Syntax

```
GET /accessors?maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### MaxResults (p. 43)

The maximum number of accessors to list.

Valid Range: Minimum value of 1. Maximum value of 50.

### NextToken (p. 43)

The pagination token that indicates the next set of results to retrieve.

Length Constraints: Maximum length of 128.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Accessors": [
    {
      "Arn": "string",
      "CreationDate": "string",
      "Id": "string",
      "Status": "string",
      "Type": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Accessors (p. 43)

An array of AccessorSummary objects that contain configuration properties for each accessor.

Type: Array of [AccessorSummary \(p. 85\)](#) objects

**[NextToken \(p. 43\)](#)**

The pagination token that indicates the next set of results to retrieve.

Type: String

Length Constraints: Maximum length of 128.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListInvitations

Returns a list of all invitations for the current AWS account.

Applies only to Hyperledger Fabric.

## Request Syntax

```
GET /invitations?maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### MaxResults (p. 45)

The maximum number of invitations to return.

Valid Range: Minimum value of 1. Maximum value of 100.

### NextToken (p. 45)

The pagination token that indicates the next set of results to retrieve.

Length Constraints: Maximum length of 128.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Invitations": [
    {
      "Arn": "string",
      "CreationDate": "string",
      "ExpirationDate": "string",
      "InvitationId": "string",
      "NetworkSummary": {
        "Arn": "string",
        "CreationDate": "string",
        "Description": "string",
        "Framework": "string",
        "FrameworkVersion": "string",
        "Id": "string",
        "Name": "string",
        "Status": "string"
      },
      "Status": "string"
    }
  ],
  "NextToken": "string"
}
```

}

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Invitations \(p. 45\)](#)

The invitations for the network.

Type: Array of [Invitation \(p. 88\)](#) objects

### [NextToken \(p. 45\)](#)

The pagination token that indicates the next set of results to retrieve.

Type: String

Length Constraints: Maximum length of 128.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServiceErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceLimitExceededException**

The maximum number of resources of that type already exist. Ensure the resources requested are within the boundaries of the service edition and your account limits.

HTTP Status Code: 429

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListMembers

Returns a list of the members in a network and properties of their configurations.

Applies only to Hyperledger Fabric.

### Request Syntax

```
GET /networks/networkId/members?  
isOwned=IsOwned&maxResults=MaxResults&name=Name&nextToken=NextToken&status=Status HTTP/1.1
```

### URI Request Parameters

The request uses the following URI parameters.

#### [IsOwned \(p. 48\)](#)

An optional Boolean value. If provided, the request is limited either to members that the current AWS account owns (`true`) or that other AWS accounts own (`false`). If omitted, all members are listed.

#### [MaxResults \(p. 48\)](#)

The maximum number of members to return in the request.

Valid Range: Minimum value of 1. Maximum value of 20.

#### [Name \(p. 48\)](#)

The optional name of the member to list.

#### [networkId \(p. 48\)](#)

The unique identifier of the network for which to list members.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

#### [NextToken \(p. 48\)](#)

The pagination token that indicates the next set of results to retrieve.

Length Constraints: Maximum length of 128.

#### [Status \(p. 48\)](#)

An optional status specifier. If provided, only members currently in this status are listed.

Valid Values: `CREATING` | `AVAILABLE` | `CREATE_FAILED` | `UPDATING` | `DELETING` | `DELETED` | `INACCESSIBLE_ENCRYPTION_KEY`

### Request Body

The request does not have a request body.

### Response Syntax

```
HTTP/1.1 200
```



Content-type: application/json

```
{
  "Members": [
    {
      "Arn": "string",
      "CreationDate": "string",
      "Description": "string",
      "Id": "string",
      "IsOwned": boolean,
      "Name": "string",
      "Status": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Members \(p. 48\)](#)

An array of `MemberSummary` objects. Each object contains details about a network member.

Type: Array of [MemberSummary \(p. 104\)](#) objects

### [NextToken \(p. 48\)](#)

The pagination token that indicates the next set of results to retrieve.

Type: String

Length Constraints: Maximum length of 128.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListNetworks

Returns information about the networks in which the current AWS account participates.

Applies to Hyperledger Fabric and Ethereum.

### Request Syntax

```
GET /networks?  
framework=Framework&maxResults=MaxResults&name=Name&nextToken=NextToken&status=Status  
HTTP/1.1
```

### URI Request Parameters

The request uses the following URI parameters.

#### [Framework \(p. 51\)](#)

An optional framework specifier. If provided, only networks of this framework type are listed.

Valid Values: HYPERLEDGER\_FABRIC | ETHEREUM

#### [MaxResults \(p. 51\)](#)

The maximum number of networks to list.

Valid Range: Minimum value of 1. Maximum value of 10.

#### [Name \(p. 51\)](#)

The name of the network.

#### [NextToken \(p. 51\)](#)

The pagination token that indicates the next set of results to retrieve.

Length Constraints: Maximum length of 128.

#### [Status \(p. 51\)](#)

An optional status specifier. If provided, only networks currently in this status are listed.

Applies only to Hyperledger Fabric.

Valid Values: CREATING | AVAILABLE | CREATE\_FAILED | DELETING | DELETED

### Request Body

The request does not have a request body.

### Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "Networks": [  
    {
```

```
    "Arn": "string",  
    "CreationDate": "string",  
    "Description": "string",  
    "Framework": "string",  
    "FrameworkVersion": "string",  
    "Id": "string",  
    "Name": "string",  
    "Status": "string"  
  }  
],  
"NextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Networks \(p. 51\)](#)

An array of `NetworkSummary` objects that contain configuration properties for each network.

Type: Array of [NetworkSummary \(p. 114\)](#) objects

### [NextToken \(p. 51\)](#)

The pagination token that indicates the next set of results to retrieve.

Type: String

Length Constraints: Maximum length of 128.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServiceErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListNodes

Returns information about the nodes within a network.

Applies to Hyperledger Fabric and Ethereum.

### Request Syntax

```
GET /networks/networkId/nodes?  
maxResults=MaxResults&memberId=MemberId&nextToken=NextToken&status=Status HTTP/1.1
```

### URI Request Parameters

The request uses the following URI parameters.

#### [MaxResults \(p. 54\)](#)

The maximum number of nodes to list.

Valid Range: Minimum value of 1. Maximum value of 20.

#### [MemberId \(p. 54\)](#)

The unique identifier of the member who owns the nodes to list.

Applies only to Hyperledger Fabric and is required for Hyperledger Fabric.

Length Constraints: Minimum length of 1. Maximum length of 32.

#### [networkId \(p. 54\)](#)

The unique identifier of the network for which to list nodes.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

#### [NextToken \(p. 54\)](#)

The pagination token that indicates the next set of results to retrieve.

Length Constraints: Maximum length of 128.

#### [Status \(p. 54\)](#)

An optional status specifier. If provided, only nodes currently in this status are listed.

Valid Values: CREATING | AVAILABLE | UNHEALTHY | CREATE\_FAILED | UPDATING |  
DELETING | DELETED | FAILED | INACCESSIBLE\_ENCRYPTION\_KEY

### Request Body

The request does not have a request body.

### Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{
  "NextToken": "string",
  "Nodes": [
    {
      "Arn": "string",
      "AvailabilityZone": "string",
      "CreationDate": "string",
      "Id": "string",
      "InstanceType": "string",
      "Status": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken \(p. 54\)](#)

The pagination token that indicates the next set of results to retrieve.

Type: String

Length Constraints: Maximum length of 128.

### [Nodes \(p. 54\)](#)

An array of `NodeSummary` objects that contain configuration properties for each node.

Type: Array of [NodeSummary \(p. 125\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# ListProposals

Returns a list of proposals for the network.

Applies only to Hyperledger Fabric.

## Request Syntax

```
GET /networks/networkId/proposals?maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [MaxResults \(p. 57\)](#)

The maximum number of proposals to return.

Valid Range: Minimum value of 1. Maximum value of 100.

### [networkId \(p. 57\)](#)

The unique identifier of the network.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### [NextToken \(p. 57\)](#)

The pagination token that indicates the next set of results to retrieve.

Length Constraints: Maximum length of 128.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Proposals": [
    {
      "Arn": "string",
      "CreationDate": "string",
      "Description": "string",
      "ExpirationDate": "string",
      "ProposalId": "string",
      "ProposedByMemberId": "string",
      "ProposedByMemberName": "string",
      "Status": "string"
    }
  ]
}
```

}

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken \(p. 57\)](#)

The pagination token that indicates the next set of results to retrieve.

Type: String

Length Constraints: Maximum length of 128.

### [Proposals \(p. 57\)](#)

The summary of each proposal made on the network.

Type: Array of [ProposalSummary \(p. 131\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## ListProposalVotes

Returns the list of votes for a specified proposal, including the value of each vote and the unique identifier of the member that cast the vote.

Applies only to Hyperledger Fabric.

### Request Syntax

```
GET /networks/networkId/proposals/proposalId/votes?  
maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

### URI Request Parameters

The request uses the following URI parameters.

#### [MaxResults \(p. 60\)](#)

The maximum number of votes to return.

Valid Range: Minimum value of 1. Maximum value of 100.

#### [networkId \(p. 60\)](#)

The unique identifier of the network.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

#### [NextToken \(p. 60\)](#)

The pagination token that indicates the next set of results to retrieve.

Length Constraints: Maximum length of 128.

#### [proposalId \(p. 60\)](#)

The unique identifier of the proposal.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### Request Body

The request does not have a request body.

### Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "NextToken": "string",  
  "ProposalVotes": [  
    {
```

```
    "MemberId": "string",  
    "MemberName": "string",  
    "Vote": "string"  
  }  
]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken \(p. 60\)](#)

The pagination token that indicates the next set of results to retrieve.

Type: String

Length Constraints: Maximum length of 128.

### [ProposalVotes \(p. 60\)](#)

The list of votes.

Type: Array of [VoteSummary \(p. 134\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTagsForResource

Returns a list of tags for the specified resource. Each tag consists of a key and optional value.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

## Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [resourceArn \(p. 63\)](#)

The Amazon Resource Name (ARN) of the resource. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:.*:.*:.*:.*:.*`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Tags \(p. 63\)](#)

The tags assigned to the resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ResourceNotReadyException**

The requested resource exists but isn't in a status that can complete the operation.

HTTP Status Code: 409

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# RejectInvitation

Rejects an invitation to join a network. This action can be called by a principal in an AWS account that has received an invitation to create a member and join a network.

Applies only to Hyperledger Fabric.

## Request Syntax

```
DELETE /invitations/invitationId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [invitationId \(p. 65\)](#)

The unique identifier of the invitation to reject.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **IllegalActionException**

HTTP Status Code: 400

### **InternalServiceErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

**InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

**ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

**ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## TagResource

Adds or overwrites the specified tags for the specified Amazon Managed Blockchain resource. Each tag consists of a key and optional value.

When you specify a tag key that already exists, the tag value is overwritten with the new value. Use `UntagResource` to remove tag keys.

A resource can have up to 50 tags. If you try to create more than 50 tags for a resource, your request fails and returns an error.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

## Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json

{
  "Tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### [resourceArn \(p. 67\)](#)

The Amazon Resource Name (ARN) of the resource. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:.*:.*:.*:.*:.*`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### [Tags \(p. 67\)](#)

The tags to assign to the specified resource. Tag values can be empty, for example, "MyTagKey" : "". You can specify multiple key-value pairs in a single request, with an overall maximum of 50 tags added to each resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ResourceNotReadyException**

The requested resource exists but isn't in a status that can complete the operation.

HTTP Status Code: 409

### **TooManyTagsException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagResource

Removes the specified tags from the Amazon Managed Blockchain resource.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

## Request Syntax

```
DELETE /tags/resourceArn?tagKeys=TagKeys HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### [resourceArn \(p. 70\)](#)

The Amazon Resource Name (ARN) of the resource. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:.*:.*:.*:.*:.*`

Required: Yes

### [TagKeys \(p. 70\)](#)

The tag keys.

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ResourceNotReadyException**

The requested resource exists but isn't in a status that can complete the operation.

HTTP Status Code: 409

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateMember

Updates a member configuration with new parameters.

Applies only to Hyperledger Fabric.

## Request Syntax

```
PATCH /networks/networkId/members/memberId HTTP/1.1  
Content-type: application/json
```

```
{  
  "LogPublishingConfiguration": {  
    "Fabric": {  
      "CaLogs": {  
        "Cloudwatch": {  
          "Enabled": boolean  
        }  
      }  
    }  
  }  
}
```

## URI Request Parameters

The request uses the following URI parameters.

### [memberId \(p. 72\)](#)

The unique identifier of the member.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### [networkId \(p. 72\)](#)

The unique identifier of the Managed Blockchain network to which the member belongs.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### [LogPublishingConfiguration \(p. 72\)](#)

Configuration properties for publishing to Amazon CloudWatch Logs.

Type: [MemberLogPublishingConfiguration \(p. 103\)](#) object

Required: No



## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServiceErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

# UpdateNode

Updates a node configuration with new parameters.

Applies only to Hyperledger Fabric.

## Request Syntax

```
PATCH /networks/networkId/nodes/nodeId HTTP/1.1  
Content-type: application/json
```

```
{  
  "LogPublishingConfiguration": {  
    "Fabric": {  
      "ChaincodeLogs": {  
        "Cloudwatch": {  
          "Enabled": boolean  
        }  
      },  
      "PeerLogs": {  
        "Cloudwatch": {  
          "Enabled": boolean  
        }  
      }  
    }  
  },  
  "MemberId": "string"  
}
```

## URI Request Parameters

The request uses the following URI parameters.

### [networkId \(p. 75\)](#)

The unique identifier of the network that the node is on.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### [nodeId \(p. 75\)](#)

The unique identifier of the node.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### [LogPublishingConfiguration \(p. 75\)](#)

Configuration properties for publishing to Amazon CloudWatch Logs.

Type: [NodeLogPublishingConfiguration \(p. 124\)](#) object

Required: No

**[MemberId \(p. 75\)](#)**

The unique identifier of the member that owns the node.

Applies only to Hyperledger Fabric.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **InternalServerErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# VoteOnProposal

Casts a vote for a specified ProposalId on behalf of a member. The member to vote as, specified by VoterMemberId, must be in the same AWS account as the principal that calls the action.

Applies only to Hyperledger Fabric.

## Request Syntax

```
POST /networks/networkId/proposals/proposalId/votes HTTP/1.1  
Content-type: application/json
```

```
{  
  "Vote": "string",  
  "VoterMemberId": "string"  
}
```

## URI Request Parameters

The request uses the following URI parameters.

### networkId (p. 78)

The unique identifier of the network.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

### proposalId (p. 78)

The unique identifier of the proposal.

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### Vote (p. 78)

The value of the vote.

Type: String

Valid Values: YES | NO

Required: Yes

### VoterMemberId (p. 78)

The unique identifier of the member casting the vote.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 138\)](#).

### **AccessDeniedException**

You don't have sufficient access to perform this action.

HTTP Status Code: 403

### **IllegalActionException**

HTTP Status Code: 400

### **InternalServiceErrorException**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

### **InvalidRequestException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

### **ResourceNotFoundException**

A requested resource doesn't exist. It may have been deleted or referenced incorrectly.

HTTP Status Code: 404

### **ThrottlingException**

The request or operation couldn't be performed because a service is throttling requests. The most common source of throttling errors is creating resources that exceed your service limit for this resource type. Request a limit increase or delete unused resources if possible.

HTTP Status Code: 429

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# Data Types

The Amazon Managed Blockchain API contains several data types that various actions use. This section describes each data type in detail.

**Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Accessor \(p. 83\)](#)
- [AccessorSummary \(p. 85\)](#)
- [ApprovalThresholdPolicy \(p. 87\)](#)
- [Invitation \(p. 88\)](#)
- [InviteAction \(p. 90\)](#)
- [LogConfiguration \(p. 91\)](#)
- [LogConfigurations \(p. 92\)](#)
- [Member \(p. 93\)](#)
- [MemberConfiguration \(p. 96\)](#)
- [MemberFabricAttributes \(p. 98\)](#)
- [MemberFabricConfiguration \(p. 99\)](#)
- [MemberFabricLogPublishingConfiguration \(p. 100\)](#)
- [MemberFrameworkAttributes \(p. 101\)](#)
- [MemberFrameworkConfiguration \(p. 102\)](#)
- [MemberLogPublishingConfiguration \(p. 103\)](#)
- [MemberSummary \(p. 104\)](#)
- [Network \(p. 106\)](#)
- [NetworkEthereumAttributes \(p. 109\)](#)
- [NetworkFabricAttributes \(p. 110\)](#)
- [NetworkFabricConfiguration \(p. 111\)](#)
- [NetworkFrameworkAttributes \(p. 112\)](#)
- [NetworkFrameworkConfiguration \(p. 113\)](#)
- [NetworkSummary \(p. 114\)](#)
- [Node \(p. 116\)](#)
- [NodeConfiguration \(p. 119\)](#)
- [NodeEthereumAttributes \(p. 120\)](#)
- [NodeFabricAttributes \(p. 121\)](#)
- [NodeFabricLogPublishingConfiguration \(p. 122\)](#)
- [NodeFrameworkAttributes \(p. 123\)](#)
- [NodeLogPublishingConfiguration \(p. 124\)](#)
- [NodeSummary \(p. 125\)](#)
- [Proposal \(p. 127\)](#)
- [ProposalActions \(p. 130\)](#)
- [ProposalSummary \(p. 131\)](#)
- [RemoveAction \(p. 133\)](#)

- [VoteSummary \(p. 134\)](#)
- [VotingPolicy \(p. 135\)](#)

# Accessor

The properties of the Accessor.

## Contents

### Arn

The Amazon Resource Name (ARN) of the accessor. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:.*:.*:.*:.*:.*`

Required: No

### BillingToken

The billing token is a property of the accessor. Use this token to make Ethereum API calls to your Ethereum node. The billing token is used to track your accessor object for billing Ethereum API requests made to your Ethereum nodes.

Type: String

Length Constraints: Fixed length of 42.

Required: No

### CreationDate

The creation date and time of the accessor.

Type: Timestamp

Required: No

### Id

The unique identifier of the accessor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### Status

The current status of the accessor.

Type: String

Valid Values: AVAILABLE | PENDING\_DELETION | DELETED

Required: No

### Tags

The tags assigned to the Accessor.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

### Type

The type of the accessor.

#### Note

Currently, accessor type is restricted to BILLING\_TOKEN.

Type: String

Valid Values: BILLING\_TOKEN

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AccessorSummary

A summary of accessor properties.

## Contents

### Arn

The Amazon Resource Name (ARN) of the accessor. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:.*:.*:.*:.*:.*`

Required: No

### CreationDate

The creation date and time of the accessor.

Type: Timestamp

Required: No

### Id

The unique identifier of the accessor.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### Status

The current status of the accessor.

Type: String

Valid Values: AVAILABLE | PENDING\_DELETION | DELETED

Required: No

### Type

The type of the accessor.

#### Note

Currently accessor type is restricted to BILLING\_TOKEN.

Type: String

Valid Values: BILLING\_TOKEN

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

## ApprovalThresholdPolicy

A policy type that defines the voting rules for the network. The rules decide if a proposal is approved. Approval may be based on criteria such as the percentage of YES votes and the duration of the proposal. The policy applies to all proposals and is specified when the network is created.

Applies only to Hyperledger Fabric.

### Contents

#### ProposalDurationInHours

The duration from the time that a proposal is created until it expires. If members cast neither the required number of YES votes to approve the proposal nor the number of NO votes required to reject it before the duration expires, the proposal is EXPIRED and `ProposalActions` aren't carried out.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 168.

Required: No

#### ThresholdComparator

Determines whether the vote percentage must be greater than the `ThresholdPercentage` or must be greater than or equal to the `ThresholdPercentage` to be approved.

Type: String

Valid Values: `GREATER_THAN` | `GREATER_THAN_OR_EQUAL_TO`

Required: No

#### ThresholdPercentage

The percentage of votes among all members that must be YES for a proposal to be approved. For example, a `ThresholdPercentage` value of 50 indicates 50%. The `ThresholdComparator` determines the precise comparison. If a `ThresholdPercentage` value of 50 is specified on a network with 10 members, along with a `ThresholdComparator` value of `GREATER_THAN`, this indicates that 6 YES votes are required for the proposal to be approved.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Invitation

An invitation to an AWS account to create a member and join the network.

Applies only to Hyperledger Fabric.

## Contents

### Arn

The Amazon Resource Name (ARN) of the invitation. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: ^arn:.\*:.\*:.\*:.\*:.\*\$

Required: No

### CreationDate

The date and time that the invitation was created.

Type: Timestamp

Required: No

### ExpirationDate

The date and time that the invitation expires. This is the `CreationDate` plus the `ProposalDurationInHours` that is specified in the `ProposalThresholdPolicy`. After this date and time, the invitee can no longer create a member and join the network using this `InvitationId`.

Type: Timestamp

Required: No

### InvitationId

The unique identifier for the invitation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### NetworkSummary

A summary of network configuration properties.

Type: [NetworkSummary \(p. 114\)](#) object

Required: No

### Status

The status of the invitation:

- PENDING - The invitee hasn't created a member to join the network, and the invitation hasn't yet expired.



- ACCEPTING - The invitee has begun creating a member, and creation hasn't yet completed.
- ACCEPTED - The invitee created a member and joined the network using the InvitationID.
- REJECTED - The invitee rejected the invitation.
- EXPIRED - The invitee neither created a member nor rejected the invitation before the ExpirationDate.

Type: String

Valid Values: PENDING | ACCEPTED | ACCEPTING | REJECTED | EXPIRED

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# InviteAction

An action to invite a specific AWS account to create a member and join the network. The InviteAction is carried out when a Proposal is APPROVED.

Applies only to Hyperledger Fabric.

## Contents

### Principal

The AWS account ID to invite.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LogConfiguration

A configuration for logging events.

## Contents

### Enabled

Indicates whether logging is enabled.

Type: Boolean

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# LogConfigurations

A collection of log configurations.

## Contents

### Cloudwatch

Parameters for publishing logs to Amazon CloudWatch Logs.

Type: [LogConfiguration \(p. 91\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Member

Member configuration properties.

Applies only to Hyperledger Fabric.

## Contents

### Arn

The Amazon Resource Name (ARN) of the member. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: ^arn: .+: .+: .+: .+: .+

Required: No

### CreationDate

The date and time that the member was created.

Type: Timestamp

Required: No

### Description

An optional description for the member.

Type: String

Length Constraints: Maximum length of 128.

Required: No

### FrameworkAttributes

Attributes relevant to a member for the blockchain framework that the Managed Blockchain network uses.

Type: [MemberFrameworkAttributes \(p. 101\)](#) object

Required: No

### Id

The unique identifier of the member.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### KmsKeyArn

The Amazon Resource Name (ARN) of the customer managed key in AWS Key Management Service (AWS KMS) that the member uses for encryption at rest. If the value of this parameter is "AWS

Owned KMS Key", the member uses an AWS owned KMS key for encryption. This parameter is inherited by the nodes that this member owns.

For more information, see [Encryption at Rest](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String

Required: No

### **LogPublishingConfiguration**

Configuration properties for logging events associated with a member.

Type: [MemberLogPublishingConfiguration \(p. 103\)](#) object

Required: No

### **Name**

The name of the member.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!-|[0-9])(?!.*-$)(?!.*?--)[a-zA-Z0-9-]+$`

Required: No

### **NetworkId**

The unique identifier of the network to which the member belongs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### **Status**

The status of a member.

- CREATING - The AWS account is in the process of creating a member.
- AVAILABLE - The member has been created and can participate in the network.
- CREATE\_FAILED - The AWS account attempted to create a member and creation failed.
- UPDATING - The member is in the process of being updated.
- DELETING - The member and all associated resources are in the process of being deleted. Either the AWS account that owns the member deleted it, or the member is being deleted as the result of an APPROVED PROPOSAL to remove the member.
- DELETED - The member can no longer participate on the network and all associated resources are deleted. Either the AWS account that owns the member deleted it, or the member is being deleted as the result of an APPROVED PROPOSAL to remove the member.
- INACCESSIBLE\_ENCRYPTION\_KEY - The member is impaired and might not function as expected because it cannot access the specified customer managed key in AWS KMS for encryption at rest. Either the KMS key was disabled or deleted, or the grants on the key were revoked.

The effect of disabling or deleting a key or of revoking a grant isn't immediate. It might take some time for the member resource to discover that the key is inaccessible. When a resource is in this state, we recommend deleting and recreating the resource.

Type: String

Valid Values: CREATING | AVAILABLE | CREATE\_FAILED | UPDATING | DELETING | DELETED | INACCESSIBLE\_ENCRYPTION\_KEY

Required: No

### Tags

Tags assigned to the member. Tags consist of a key and optional value.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MemberConfiguration

Configuration properties of the member.

Applies only to Hyperledger Fabric.

## Contents

### FrameworkConfiguration

Configuration properties of the blockchain framework relevant to the member.

Type: [MemberFrameworkConfiguration \(p. 102\)](#) object

Required: Yes

#### Name

The name of the member.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!-|[0-9])(?!.*-$)(?!.*?--)[a-zA-Z0-9-]+$`

Required: Yes

#### Description

An optional description of the member.

Type: String

Length Constraints: Maximum length of 128.

Required: No

#### KmsKeyArn

The Amazon Resource Name (ARN) of the customer managed key in AWS Key Management Service (AWS KMS) to use for encryption at rest in the member. This parameter is inherited by any nodes that this member creates. For more information, see [Encryption at Rest](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Use one of the following options to specify this parameter:

- **Undefined or empty string** - By default, use an AWS KMS key that is owned and managed by AWS on your behalf.
- **A valid symmetric customer managed KMS key** - Use the specified KMS key in your account that you create, own, and manage.

Amazon Managed Blockchain doesn't support asymmetric keys. For more information, see [Using symmetric and asymmetric keys](#) in the *AWS Key Management Service Developer Guide*.

The following is an example of a KMS key ARN: `arn:aws:kms:us-east-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.



Pattern: `^arn:..+:.+:.+:.+:.+.`

Required: No

### LogPublishingConfiguration

Configuration properties for logging events associated with a member of a Managed Blockchain network.

Type: [MemberLogPublishingConfiguration \(p. 103\)](#) object

Required: No

### Tags

Tags assigned to the member. Tags consist of a key and optional value.

When specifying tags during creation, you can specify multiple key-value pairs in a single request, with an overall maximum of 50 tags added to each resource.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MemberFabricAttributes

Attributes of Hyperledger Fabric for a member in a Managed Blockchain network using the Hyperledger Fabric framework.

## Contents

### **AdminUsername**

The user name for the initial administrator user for the member.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16.

Pattern: `^[a-zA-Z][a-zA-Z0-9]*$`

Required: No

### **CaEndpoint**

The endpoint used to access the member's certificate authority.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MemberFabricConfiguration

Configuration properties for Hyperledger Fabric for a member in a Managed Blockchain network that is using the Hyperledger Fabric framework.

## Contents

### AdminPassword

The password for the member's initial administrative user. The AdminPassword must be at least 8 characters long and no more than 32 characters. It must contain at least one uppercase letter, one lowercase letter, and one digit. It cannot have a single quotation mark ('), a double quotation marks ("), a forward slash(/), a backward slash(\), @, or a space.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 32.

Pattern: `^(?=.*[a-z])(?=.*[A-Z])(?=.*\d)(?!.*['\"/])[a-zA-Z0-9\S]*$`

Required: Yes

### AdminUsername

The user name for the member's initial administrative user.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16.

Pattern: `^[a-zA-Z][a-zA-Z0-9]*$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MemberFabricLogPublishingConfiguration

Configuration properties for logging events associated with a member of a Managed Blockchain network using the Hyperledger Fabric framework.

## Contents

### CaLogs

Configuration properties for logging events associated with a member's Certificate Authority (CA). CA logs help you determine when a member in your account joins the network, or when new peers register with a member CA.

Type: [LogConfigurations \(p. 92\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MemberFrameworkAttributes

Attributes relevant to a member for the blockchain framework that the Managed Blockchain network uses.

## Contents

### Fabric

Attributes of Hyperledger Fabric relevant to a member on a Managed Blockchain network that uses Hyperledger Fabric.

Type: [MemberFabricAttributes \(p. 98\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MemberFrameworkConfiguration

Configuration properties relevant to a member for the blockchain framework that the Managed Blockchain network uses.

## Contents

### Fabric

Attributes of Hyperledger Fabric for a member on a Managed Blockchain network that uses Hyperledger Fabric.

Type: [MemberFabricConfiguration \(p. 99\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MemberLogPublishingConfiguration

Configuration properties for logging events associated with a member of a Managed Blockchain network.

## Contents

### Fabric

Configuration properties for logging events associated with a member of a Managed Blockchain network using the Hyperledger Fabric framework.

Type: [MemberFabricLogPublishingConfiguration \(p. 100\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MemberSummary

A summary of configuration properties for a member.

Applies only to Hyperledger Fabric.

## Contents

### Arn

The Amazon Resource Name (ARN) of the member. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:.*:.*:.*:.*:.*`

Required: No

### CreationDate

The date and time that the member was created.

Type: Timestamp

Required: No

### Description

An optional description of the member.

Type: String

Length Constraints: Maximum length of 128.

Required: No

### Id

The unique identifier of the member.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### IsOwned

An indicator of whether the member is owned by your AWS account or a different AWS account.

Type: Boolean

Required: No

### Name

The name of the member.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.



Pattern: `^(?!-[0-9])(?!.*-)(?!.*?--)[a-zA-Z0-9-]+$`

Required: No

### Status

The status of the member.

- **CREATING** - The AWS account is in the process of creating a member.
- **AVAILABLE** - The member has been created and can participate in the network.
- **CREATE\_FAILED** - The AWS account attempted to create a member and creation failed.
- **UPDATING** - The member is in the process of being updated.
- **DELETING** - The member and all associated resources are in the process of being deleted. Either the AWS account that owns the member deleted it, or the member is being deleted as the result of an **APPROVED PROPOSAL** to remove the member.
- **DELETED** - The member can no longer participate on the network and all associated resources are deleted. Either the AWS account that owns the member deleted it, or the member is being deleted as the result of an **APPROVED PROPOSAL** to remove the member.
- **INACCESSIBLE\_ENCRYPTION\_KEY** - The member is impaired and might not function as expected because it cannot access the specified customer managed key in AWS Key Management Service (AWS KMS) for encryption at rest. Either the KMS key was disabled or deleted, or the grants on the key were revoked.

The effect of disabling or deleting a key or of revoking a grant isn't immediate. It might take some time for the member resource to discover that the key is inaccessible. When a resource is in this state, we recommend deleting and recreating the resource.

Type: String

Valid Values: **CREATING** | **AVAILABLE** | **CREATE\_FAILED** | **UPDATING** | **DELETING** | **DELETED** | **INACCESSIBLE\_ENCRYPTION\_KEY**

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Network

Network configuration properties.

## Contents

### Arn

The Amazon Resource Name (ARN) of the network. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:.*:.*:.*:.*:.*`

Required: No

### CreationDate

The date and time that the network was created.

Type: Timestamp

Required: No

### Description

Attributes of the blockchain framework for the network.

Type: String

Length Constraints: Maximum length of 128.

Required: No

### Framework

The blockchain framework that the network uses.

Type: String

Valid Values: HYPERLEDGER\_FABRIC | ETHEREUM

Required: No

### FrameworkAttributes

Attributes of the blockchain framework that the network uses.

Type: [NetworkFrameworkAttributes \(p. 112\)](#) object

Required: No

### FrameworkVersion

The version of the blockchain framework that the network uses.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8.

Required: No

### **Id**

The unique identifier of the network.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### **Name**

The name of the network.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: .\*\S.\*

Required: No

### **Status**

The current status of the network.

Type: String

Valid Values: CREATING | AVAILABLE | CREATE\_FAILED | DELETING | DELETED

Required: No

### **Tags**

Tags assigned to the network. Each tag consists of a key and optional value.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

### **VotingPolicy**

The voting rules that the network uses to decide if a proposal is accepted.

Type: [VotingPolicy \(p. 135\)](#) object

Required: No

### **VpcEndpointServiceName**

The VPC endpoint service name of the VPC endpoint service of the network. Members use the VPC endpoint service name to create a VPC endpoint to access network resources.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NetworkEthereumAttributes

Attributes of Ethereum for a network.

## Contents

### ChainId

The Ethereum CHAIN\_ID associated with the Ethereum network. Chain IDs are as follows:

- mainnet = 1
- goerli = 5
- rinkeby = 4

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NetworkFabricAttributes

Attributes of Hyperledger Fabric for a network.

## Contents

### Edition

The edition of Amazon Managed Blockchain that Hyperledger Fabric uses. For more information, see [Amazon Managed Blockchain Pricing](#).

Type: String

Valid Values: STARTER | STANDARD

Required: No

### OrderingServiceEndpoint

The endpoint of the ordering service for the network.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NetworkFabricConfiguration

Hyperledger Fabric configuration properties for the network.

## Contents

### Edition

The edition of Amazon Managed Blockchain that the network uses. For more information, see [Amazon Managed Blockchain Pricing](#).

Type: String

Valid Values: STARTER | STANDARD

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NetworkFrameworkAttributes

Attributes relevant to the network for the blockchain framework that the network uses.

## Contents

### Ethereum

Attributes of an Ethereum network for Managed Blockchain resources participating in an Ethereum network.

Type: [NetworkEthereumAttributes \(p. 109\)](#) object

Required: No

### Fabric

Attributes of Hyperledger Fabric for a Managed Blockchain network that uses Hyperledger Fabric.

Type: [NetworkFabricAttributes \(p. 110\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# NetworkFrameworkConfiguration

Configuration properties relevant to the network for the blockchain framework that the network uses.

## Contents

### Fabric

Hyperledger Fabric configuration properties for a Managed Blockchain network that uses Hyperledger Fabric.

Type: [NetworkFabricConfiguration \(p. 111\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NetworkSummary

A summary of network configuration properties.

## Contents

### Arn

The Amazon Resource Name (ARN) of the network. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn:.*:.*:.*:.*:.*`

Required: No

### CreationDate

The date and time that the network was created.

Type: Timestamp

Required: No

### Description

An optional description of the network.

Type: String

Length Constraints: Maximum length of 128.

Required: No

### Framework

The blockchain framework that the network uses.

Type: String

Valid Values: HYPERLEDGER\_FABRIC | ETHEREUM

Required: No

### FrameworkVersion

The version of the blockchain framework that the network uses.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8.

Required: No

### Id

The unique identifier of the network.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

**Name**

The name of the network.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `.*\S.*`

Required: No

**Status**

The current status of the network.

Type: String

Valid Values: `CREATING` | `AVAILABLE` | `CREATE_FAILED` | `DELETING` | `DELETED`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Node

Configuration properties of a node.

## Contents

### Arn

The Amazon Resource Name (ARN) of the node. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: ^arn:.\*:.\*:.\*:.\*:.\*\$

Required: No

### AvailabilityZone

The Availability Zone in which the node exists. Required for Ethereum nodes.

Type: String

Required: No

### CreationDate

The date and time that the node was created.

Type: Timestamp

Required: No

### FrameworkAttributes

Attributes of the blockchain framework being used.

Type: [NodeFrameworkAttributes \(p. 123\)](#) object

Required: No

### Id

The unique identifier of the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### InstanceType

The instance type of the node.

Type: String

Required: No

### KmsKeyArn

The Amazon Resource Name (ARN) of the customer managed key in AWS Key Management Service (AWS KMS) that the node uses for encryption at rest. If the value of this parameter is "AWS Owned

KMS Key", the node uses an AWS owned KMS key for encryption. The node inherits this parameter from the member that it belongs to.

For more information, see [Encryption at Rest](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Applies only to Hyperledger Fabric.

Type: String

Required: No

### **LogPublishingConfiguration**

Configuration properties for logging events associated with a peer node on a Hyperledger Fabric network on Managed Blockchain.

Type: [NodeLogPublishingConfiguration \(p. 124\)](#) object

Required: No

### **MemberId**

The unique identifier of the member to which the node belongs.

Applies only to Hyperledger Fabric.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### **NetworkId**

The unique identifier of the network that the node is on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### **StateDB**

The state database that the node uses. Values are LevelDB or CouchDB.

Applies only to Hyperledger Fabric.

Type: String

Valid Values: LevelDB | CouchDB

Required: No

### **Status**

The status of the node.

- CREATING - The AWS account is in the process of creating a node.
- AVAILABLE - The node has been created and can participate in the network.
- UNHEALTHY - The node is impaired and might not function as expected. Amazon Managed Blockchain automatically finds nodes in this state and tries to recover them. If a node is recoverable, it returns to AVAILABLE. Otherwise, it moves to FAILED status.
- CREATE\_FAILED - The AWS account attempted to create a node and creation failed.

- UPDATING - The node is in the process of being updated.
- DELETING - The node is in the process of being deleted.
- DELETED - The node can no longer participate on the network.
- FAILED - The node is no longer functional, cannot be recovered, and must be deleted.
- INACCESSIBLE\_ENCRYPTION\_KEY - The node is impaired and might not function as expected because it cannot access the specified customer managed key in AWS KMS for encryption at rest. Either the KMS key was disabled or deleted, or the grants on the key were revoked.

The effect of disabling or deleting a key or of revoking a grant isn't immediate. It might take some time for the node resource to discover that the key is inaccessible. When a resource is in this state, we recommend deleting and recreating the resource.

Type: String

Valid Values: CREATING | AVAILABLE | UNHEALTHY | CREATE\_FAILED | UPDATING | DELETING | DELETED | FAILED | INACCESSIBLE\_ENCRYPTION\_KEY

Required: No

### Tags

Tags assigned to the node. Each tag consists of a key and optional value.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NodeConfiguration

Configuration properties of a node.

## Contents

### **InstanceType**

The Amazon Managed Blockchain instance type for the node.

Type: String

Required: Yes

### **AvailabilityZone**

The Availability Zone in which the node exists. Required for Ethereum nodes.

Type: String

Required: No

### **LogPublishingConfiguration**

Configuration properties for logging events associated with a peer node on a Hyperledger Fabric network on Managed Blockchain.

Type: [NodeLogPublishingConfiguration \(p. 124\)](#) object

Required: No

### **StateDB**

The state database that the node uses. Values are LevelDB or CouchDB. When using an Amazon Managed Blockchain network with Hyperledger Fabric version 1.4 or later, the default is CouchDB.

Applies only to Hyperledger Fabric.

Type: String

Valid Values: LevelDB | CouchDB

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NodeEthereumAttributes

Attributes of an Ethereum node.

## Contents

### HttpEndpoint

The endpoint on which the Ethereum node listens to run Ethereum API methods over HTTP connections from a client. Use this endpoint in client code for smart contracts when using an HTTP connection. Connections to this endpoint are authenticated using [Signature Version 4](#).

Type: String

Required: No

### WebSocketEndpoint

The endpoint on which the Ethereum node listens to run Ethereum JSON-RPC methods over WebSocket connections from a client. Use this endpoint in client code for smart contracts when using a WebSocket connection. Connections to this endpoint are authenticated using [Signature Version 4](#).

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# NodeFabricAttributes

Attributes of Hyperledger Fabric for a peer node on a Hyperledger Fabric network on Managed Blockchain.

## Contents

### **PeerEndpoint**

The endpoint that identifies the peer node for all services except peer channel-based event services.

Type: String

Required: No

### **PeerEventEndpoint**

The endpoint that identifies the peer node for peer channel-based event services.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NodeFabricLogPublishingConfiguration

Configuration properties for logging events associated with a peer node owned by a member in a Managed Blockchain network.

## Contents

### ChaincodeLogs

Configuration properties for logging events associated with chaincode execution on a peer node. Chaincode logs contain the results of instantiating, invoking, and querying the chaincode. A peer can run multiple instances of chaincode. When enabled, a log stream is created for all chaincodes, with an individual log stream for each chaincode.

Type: [LogConfigurations \(p. 92\)](#) object

Required: No

### PeerLogs

Configuration properties for a peer node log. Peer node logs contain messages generated when your client submits transaction proposals to peer nodes, requests to join channels, enrolls an admin peer, and lists the chaincode instances on a peer node.

Type: [LogConfigurations \(p. 92\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NodeFrameworkAttributes

Attributes relevant to a node on a Managed Blockchain network for the blockchain framework that the network uses.

## Contents

### Ethereum

Attributes of Ethereum for a node on a Managed Blockchain network that uses Ethereum.

Type: [NodeEthereumAttributes \(p. 120\)](#) object

Required: No

### Fabric

Attributes of Hyperledger Fabric for a peer node on a Managed Blockchain network that uses Hyperledger Fabric.

Type: [NodeFabricAttributes \(p. 121\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NodeLogPublishingConfiguration

Configuration properties for logging events associated with a peer node on a Hyperledger Fabric network on Managed Blockchain.

## Contents

### Fabric

Configuration properties for logging events associated with a node that is owned by a member of a Managed Blockchain network using the Hyperledger Fabric framework.

Type: [NodeFabricLogPublishingConfiguration \(p. 122\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NodeSummary

A summary of configuration properties for a node.

## Contents

### Arn

The Amazon Resource Name (ARN) of the node. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: ^arn: .+: .+: .+: .+: .+

Required: No

### AvailabilityZone

The Availability Zone in which the node exists.

Type: String

Required: No

### CreationDate

The date and time that the node was created.

Type: Timestamp

Required: No

### Id

The unique identifier of the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### InstanceType

The EC2 instance type for the node.

Type: String

Required: No

### Status

The status of the node.

Type: String

Valid Values: CREATING | AVAILABLE | UNHEALTHY | CREATE\_FAILED | UPDATING | DELETING | DELETED | FAILED | INACCESSIBLE\_ENCRYPTION\_KEY

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Proposal

Properties of a proposal on a Managed Blockchain network.

Applies only to Hyperledger Fabric.

## Contents

### Actions

The actions to perform on the network if the proposal is APPROVED.

Type: [ProposalActions \(p. 130\)](#) object

Required: No

### Arn

The Amazon Resource Name (ARN) of the proposal. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `^arn: .+ : .+ : .+ : .+ : .+`

Required: No

### CreationDate

The date and time that the proposal was created.

Type: Timestamp

Required: No

### Description

The description of the proposal.

Type: String

Length Constraints: Maximum length of 128.

Required: No

### ExpirationDate

The date and time that the proposal expires. This is the `CreationDate` plus the `ProposalDurationInHours` that is specified in the `ProposalThresholdPolicy`. After this date and time, if members haven't cast enough votes to determine the outcome according to the voting policy, the proposal is EXPIRED and Actions aren't carried out.

Type: Timestamp

Required: No

### NetworkId

The unique identifier of the network for which the proposal is made.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

**NoVoteCount**

The current total of NO votes cast on the proposal by members.

Type: Integer

Required: No

**OutstandingVoteCount**

The number of votes remaining to be cast on the proposal by members. In other words, the number of members minus the sum of YES votes and NO votes.

Type: Integer

Required: No

**ProposalId**

The unique identifier of the proposal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

**ProposedByMemberId**

The unique identifier of the member that created the proposal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

**ProposedByMemberName**

The name of the member that created the proposal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!-|[0-9])(?!.*-$)(?!.*?--)[a-zA-Z0-9-]+$`

Required: No

**Status**

The status of the proposal. Values are as follows:

- IN\_PROGRESS - The proposal is active and open for member voting.
- APPROVED - The proposal was approved with sufficient YES votes among members according to the VotingPolicy specified for the Network. The specified proposal actions are carried out.
- REJECTED - The proposal was rejected with insufficient YES votes among members according to the VotingPolicy specified for the Network. The specified ProposalActions aren't carried out.
- EXPIRED - Members didn't cast the number of votes required to determine the proposal outcome before the proposal expired. The specified ProposalActions aren't carried out.



- **ACTION\_FAILED** - One or more of the specified `ProposalActions` in a proposal that was approved couldn't be completed because of an error. The **ACTION\_FAILED** status occurs even if only one `ProposalAction` fails and other actions are successful.

Type: String

Valid Values: `IN_PROGRESS` | `APPROVED` | `REJECTED` | `EXPIRED` | `ACTION_FAILED`

Required: No

### Tags

Tags assigned to the proposal. Each tag consists of a key and optional value.

For more information about tags, see [Tagging Resources](#) in the *Amazon Managed Blockchain Ethereum Developer Guide*, or [Tagging Resources](#) in the *Amazon Managed Blockchain Hyperledger Fabric Developer Guide*.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

### YesVoteCount

The current total of YES votes cast on the proposal by members.

Type: Integer

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ProposalActions

The actions to carry out if a proposal is APPROVED.

Applies only to Hyperledger Fabric.

## Contents

### Invitations

The actions to perform for an APPROVED proposal to invite an AWS account to create a member and join the network.

Type: Array of [InviteAction \(p. 90\)](#) objects

Required: No

### Removals

The actions to perform for an APPROVED proposal to remove a member from the network, which deletes the member and all associated member resources from the network.

Type: Array of [RemoveAction \(p. 133\)](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ProposalSummary

Properties of a proposal.

Applies only to Hyperledger Fabric.

## Contents

### Arn

The Amazon Resource Name (ARN) of the proposal. For more information about ARNs and their format, see [Amazon Resource Names \(ARNs\)](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: ^arn:..+:.+:.+:.+:.+.

Required: No

### CreationDate

The date and time that the proposal was created.

Type: Timestamp

Required: No

### Description

The description of the proposal.

Type: String

Length Constraints: Maximum length of 128.

Required: No

### ExpirationDate

The date and time that the proposal expires. This is the `CreationDate` plus the `ProposalDurationInHours` that is specified in the `ProposalThresholdPolicy`. After this date and time, if members haven't cast enough votes to determine the outcome according to the voting policy, the proposal is EXPIRED and Actions aren't carried out.

Type: Timestamp

Required: No

### ProposalId

The unique identifier of the proposal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### ProposedByMemberId

The unique identifier of the member that created the proposal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

#### **ProposedByMemberName**

The name of the member that created the proposal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!-|[0-9])(?!.*-$)(?!.*?--)[a-zA-Z0-9-]+$`

Required: No

#### **Status**

The status of the proposal. Values are as follows:

- **IN\_PROGRESS** - The proposal is active and open for member voting.
- **APPROVED** - The proposal was approved with sufficient YES votes among members according to the `VotingPolicy` specified for the Network. The specified proposal actions are carried out.
- **REJECTED** - The proposal was rejected with insufficient YES votes among members according to the `VotingPolicy` specified for the Network. The specified `ProposalActions` aren't carried out.
- **EXPIRED** - Members didn't cast the number of votes required to determine the proposal outcome before the proposal expired. The specified `ProposalActions` aren't carried out.
- **ACTION\_FAILED** - One or more of the specified `ProposalActions` in a proposal that was approved couldn't be completed because of an error.

Type: String

Valid Values: `IN_PROGRESS | APPROVED | REJECTED | EXPIRED | ACTION_FAILED`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RemoveAction

An action to remove a member from a Managed Blockchain network as the result of a removal proposal that is APPROVED. The member and all associated resources are deleted from the network.

Applies only to Hyperledger Fabric.

## Contents

### MemberId

The unique identifier of the member to remove.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# VoteSummary

Properties of an individual vote that a member cast for a proposal.

Applies only to Hyperledger Fabric.

## Contents

### MemberId

The unique identifier of the member that cast the vote.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: No

### MemberName

The name of the member that cast the vote.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!-[0-9])(?!.*-)$)(?!.*?--)[a-zA-Z0-9-]+$`

Required: No

### Vote

The vote value, either YES or NO.

Type: String

Valid Values: YES | NO

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# VotingPolicy

The voting rules for the network to decide if a proposal is accepted

Applies only to Hyperledger Fabric.

## Contents

### ApprovalThresholdPolicy

Defines the rules for the network for voting on proposals, such as the percentage of YES votes required for the proposal to be approved and the duration of the proposal. The policy applies to all proposals and is specified when the network is created.

Type: [ApprovalThresholdPolicy \(p. 87\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## Action

The action to be performed.

Type: string

Required: Yes

## Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

## X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.



Type: string

Required: Conditional

**X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

**X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

**X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 400

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

## **InvalidClientTokenId**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

## **InvalidParameterCombination**

Parameters that must not be used together were used together.

HTTP Status Code: 400

## **InvalidParameterValue**

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

## **InvalidQueryParameter**

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

## **MalformedQueryString**

The query string contains a syntax error.

HTTP Status Code: 404

## **MissingAction**

The request is missing an action or a required parameter.

HTTP Status Code: 400

**MissingAuthenticationToken**

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

**MissingParameter**

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

**NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 400

**OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

**RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

**ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

**ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

**ValidationError**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400