

1520

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- · Watertight, crushproof, and dustproof
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- · Comfortable rubber over-molded handle
- Easy open Double Throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1520 Standard



1524 With Padded Dividers



1526With Convertible Travel Bag



1520NF No Foam



1520WF With Foam

DIMENSIONS

Interior (L x W x D) 18.06 x 12.89" x 6.72 (45.9 x 32.7 x 17.1 cm) Exterior (L x W x D) 19.78 x 15.77" x 7.41 (50.2 x 40.1 x 18.8 cm)

 Lid Depth
 1.79" (4.5 cm)

 Bottom Depth
 4.93" (12.5 cm)

 Total Depth
 6.72" (17.1 cm)

 Int Volume
 0.91 ft³ (0.026 m³)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com

COLORS

Black

Document created on 06-06-19

Yellow

OD Green

Desert Tan

Orange

WEIGHT

 Weight With Foam
 9.35 lbs (4.2 kg)

 Weight Empty
 8.29 lbs (3.8 kg)

 Buoyancy
 63.00 lbs (28.6 kg)

 Master Pack Weight
 23.30 lbs (10.6 kg)

Silver

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41 STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid) 1.75" Convolute
Layer 2 (Base) 0.75" Pad

Layer 3 (Base) 4.00" Pick N Pluck

OTHER

Master Pack2NameplateyesMilitaryyes

ACCESSORIES