



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel


Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 27.8

SPEChpc 2021_tny_peak = 30.2

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023



Results Table

Benchmark	Base										Peak							
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
505.lbm_t	OMP	32	14	65.8	34.2	62.7	35.9	<u>62.8</u>	<u>35.8</u>	OMP	448	1	<u>54.0</u>	<u>41.6</u>	54.0	41.7	54.3	41.4
513.soma_t	OMP	32	14	94.4	39.2	<u>95.3</u>	<u>38.8</u>	102	36.3	OMP	16	28	90.5	40.9	90.9	40.7	<u>90.7</u>	<u>40.8</u>
518.tealeaf_t	OMP	32	14	<u>90.2</u>	<u>18.3</u>	91.6	18.0	88.7	18.6	OMP	32	14	<u>90.2</u>	<u>18.3</u>	91.6	18.0	88.7	18.6
519.cvlleaf_t	OMP	32	14	96.1	17.2	95.1	17.4	<u>95.3</u>	<u>17.3</u>	OMP	32	14	86.1	19.2	84.4	19.5	<u>84.6</u>	<u>19.5</u>
521.miniswp_t	OMP	32	14	66.2	24.2	66.3	24.1	<u>66.3</u>	<u>24.1</u>	OMP	16	28	59.0	27.1	<u>59.2</u>	<u>27.0</u>	59.6	26.9
528.pot3d_t	OMP	32	14	<u>105</u>	<u>20.3</u>	104	20.5	105	20.3	OMP	32	14	<u>105</u>	<u>20.3</u>	104	20.5	105	20.3
532.sph_exa_t	OMP	32	14	<u>60.4</u>	<u>32.3</u>	60.0	32.5	60.7	32.1	OMP	448	1	50.7	38.4	51.3	38.0	<u>51.2</u>	<u>38.1</u>
534.hpgmgfv_t	OMP	32	14	<u>70.8</u>	<u>16.6</u>	70.9	16.6	70.6	16.6	OMP	64	7	<u>62.2</u>	<u>18.9</u>	62.6	18.8	62.0	18.9
535.weather_t	OMP	32	14	<u>37.2</u>	<u>86.6</u>	37.0	87.1	37.4	86.3	OMP	32	14	<u>37.2</u>	<u>86.6</u>	37.0	87.1	37.4	86.3

SPEChpc 2021_tny_base = 27.8

SPEChpc 2021_tny_peak = 30.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 27.8

SPEChpc 2021_tny_peak = 30.2

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: Intel Server D50DNP2MFALACB (Xeon 8480+)
Interconnect: Mellanox HDR
Compute Nodes Used: 4
Total Chips: 8
Total Cores: 448
Total Threads: 896
Total Memory: 2 TB
Max. Peak Threads: 28

Software Summary

Compiler: Intel oneAPI Compiler 2023.1.0
MPI Library: Intel MPI Library 2021.9 for Linux OS
Other MPI Info: None
Other Software: None
Base Parallel Model: OMP
Base Ranks Run: 32
Base Threads Run: 14
Peak Parallel Models: OMP
Minimum Peak Ranks: 16
Maximum Peak Ranks: 448
Max. Peak Threads: 28
Min. Peak Threads: 1

Node Description: Intel Server D50DNP2MFALACB (Xeon 8480+)

Hardware

Number of nodes: 4
Uses of the node: Compute
Vendor: Intel
Model: Intel Server D50DNP2MFALACB (Xeon 8480+)
CPU Name: Intel Xeon Platinum 8480+
CPU(s) orderable: 1, 2 chips
Chips enabled: 2
Cores enabled: 112
Cores per chip: 56
Threads per core: 2
CPU Characteristics: Turbo Boost Technology up to 3.8 GHz
CPU MHz: 2000
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 2 MB I+D on chip per core
L3 Cache: 105 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (16 x 32 GB 2Rx8 PC5-4800B)
Disk Subsystem: 1 x 1 TB NVMe U.2 2.5" SSD
Other Hardware: None
Accel Count: None
Accel Model: None
Accel Vendor: None
Accel Type: None
Accel Connection: None
Accel ECC enabled: None
Accel Description: None
Adapter: Mellanox ConnectX-6 HDR
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 200Gbit/s
Ports Used: 1
Interconnect Type: Mellanox HDR

Software

Accelerator Driver: None
Adapter: Mellanox ConnectX-6 HDR
Adapter Driver: 5.9-0.5.5
Adapter Firmware: 20.36.1010
Operating System: Rocky Linux 8.7 (Green Obsidian)
4.18.0-372.32.1.el8_6.crt3.x86_64
Local File System: NFS
Shared File System: PANASAS FS
System State: Multi-user
Other Software: None



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 27.8

SPEChpc 2021_tny_peak = 30.2

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Interconnect Description: Mellanox HDR

Hardware

Software

Vendor: Mellanox
Model: Mellanox HDR
Switch Model: Mellanox MQM8790-HS2F Quantum HDR InfiniBand Switch
Number of Switches: 18
Number of Ports: 40
Data Rate: 200 Gbit/s
Firmware: 20.36.1010
Topology: Fat-tree
Primary Use: MPI Traffic

: --

Submit Notes

The config file option 'submit' was used.

General Notes

The PANASAS filesystem as described on this result page was formerly generally available. At the time of this publication, it may not be shipping, and/or may not be supported, and/or may fail to meet other tests of General Availability described in the SPEC HPG Policy document, <http://www.spec.org/hpg/policy.html>

Compiler Version Notes

=====
CXXC 532.sph_exa_t(base, peak)

Intel(R) oneAPI DPC++/C++ Compiler 2023.1.0 (2023.1.0.20230320)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir:
/global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm
Configuration file:
/global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm/./bin/icpx.cfg

=====
CC 505.lbm_t(base, peak) 513.soma_t(base, peak) 518.tealeaf_t(base, peak)
521.miniswp_t(base, peak) 534.hpgmgfv_t(base)

Intel(R) oneAPI DPC++/C++ Compiler 2023.1.0 (2023.1.0.20230320)
Target: x86_64-unknown-linux-gnu

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 27.8

SPEChpc 2021_tny_peak = 30.2

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Compiler Version Notes (Continued)

Thread model: posix
InstalledDir:

/global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm
Configuration file:
/global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm/./bin/icx.cfg

=====
CC 534.hpgmgfv_t(peak)
=====

icc: remark #10441: The Intel(R) C++ Compiler Classic (ICC) is deprecated and will be removed from product release in the second half of 2023. The Intel(R) oneAPI DPC++/C++ Compiler (ICX) is the recommended compiler moving forward. Please transition to use this compiler. Use '-diag-disable=10441' to disable this message.

icc: command line warning #10148: option '-Wno-incompatible-function-pointer-types' not supported

icc (ICC) 2021.9.0 20230302
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

=====
FC 519.clvleaf_t(peak)
=====

ifort (IFORT) 2021.9.0 20230302
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

=====
FC 519.clvleaf_t(base) 528.pot3d_t(base, peak) 535.weather_t(base, peak)
=====

ifx (IFX) 2023.1.0 20230320
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

Base Compiler Invocation

C benchmarks:
mpiicc -cc=icx

C++ benchmarks:
mpicpc -cxx=icpx

Fortran benchmarks:
mpiifort -fc=ifx



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 27.8

SPEChpc 2021_tny_peak = 30.2

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Base Portability Flags

```
505.lbm_t: -lstdc++ -std=c++14
513.soma_t: -lstdc++ -std=c++14
518.tealeaf_t: -lstdc++ -std=c++14
521.miniswp_t: -lstdc++ -std=c++14
534.hpgmgfv_t: -lstdc++ -std=c++14
```

Base Optimization Flags

C benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto
-funroll-loops
```

C++ benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto
-funroll-loops
```

Fortran benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto
-funroll-loops -nostandard-realloc-lhs -align array64byte
```

Base Other Flags

C benchmarks (except as noted below):

```
-Ispecmpitime -Wno-incompatible-function-pointer-types
```

```
521.miniswp_t: -Ispecmpitime/ -Wno-incompatible-function-pointer-types
```

```
534.hpgmgfv_t: -Ispecmpitime -Wno-incompatible-function-pointer-types
```

C++ benchmarks:

```
-Ispecmpitime
```

Fortran benchmarks:

```
519.clvleaf_t: -Ispecmpitime
```



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 27.8

SPEChpc 2021_tny_peak = 30.2

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Peak Compiler Invocation

C benchmarks (except as noted below):

```
mpiicc -cc=icx
```

```
534.hpgmgfv_t: mpiicc
```

C++ benchmarks:

```
mpiicpc -cxx=icpx
```

Fortran benchmarks (except as noted below):

```
mpiifort -fc=ifx
```

```
519.clvleaf_t: mpiifort
```

Peak Portability Flags

```
505.lbm_t: -lstdc++ -std=c++14  
513.soma_t: -lstdc++ -std=c++14  
518.tealeaf_t: -lstdc++ -std=c++14  
521.miniswp_t: -lstdc++ -std=c++14  
534.hpgmgfv_t: -lstdc++ -std=c++14
```

Peak Optimization Flags

C benchmarks:

```
505.lbm_t: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp  
-ffast-math -flto -funroll-loops
```

```
513.soma_t: Same as 505.lbm_t
```

```
518.tealeaf_t: basepeak = yes
```

```
521.miniswp_t: Same as 505.lbm_t
```

```
534.hpgmgfv_t: -O3 -Ofast -xCORE-AVX512 -ansi-alias -qopenmp -ipo  
-qopt-zmm-usage=high  
-qopt-multiple-gather-scatter-by-shuffles
```

C++ benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto
```

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 27.8

SPEChpc 2021_tny_peak = 30.2

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Peak Optimization Flags (Continued)

C++ benchmarks (continued):

-funroll-loops

Fortran benchmarks:

519.clvleaf_t: -O3 -Ofast -xCORE-AVX512 -ansi-alias -qopenmp -ipo
-qopt-zmm-usage=high
-qopt-multiple-gather-scatter-by-shuffles
-nostandard-realloc-lhs -align array64byte

528.pot3d_t: basepeak = yes

535.weather_t: basepeak = yes

Peak Other Flags

C benchmarks (except as noted below):

-Ispecmpitime -Wno-incompatible-function-pointer-types

521.miniswp_t: -Ispecmpitime/ -Wno-incompatible-function-pointer-types

534.hpgmgfv_t: -Ispecmpitime -Wno-incompatible-function-pointer-types

C++ benchmarks:

-Ispecmpitime

Fortran benchmarks:

519.clvleaf_t: -Ispecmpitime

The flags file that was used to format this result can be browsed at

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2023-07-08 05:16:27-0400.

Report generated on 2023-08-16 15:01:52 by hpc2021 PDF formatter v1.0.3.

Originally published on 2023-08-16.