



# SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Intel


Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021\_med\_base = 2.53

SPEChpc 2021\_med\_peak = 2.58

hpc2021 License: 13  
Test Sponsor: Intel  
Tested by: Intel

Test Date: Jul-2023  
Hardware Availability: Jan-2023  
Software Availability: Apr-2023



## Results Table

Benchmark	Base										Peak							
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
705.lbm_m	OMP	512	7	<b>324</b>	<b>3.78</b>	323	3.79	325	3.77	OMP	512	7	<b>324</b>	<b>3.78</b>	323	3.79	325	3.77
718.tealeaf_m	OMP	512	7	733	1.84	734	1.84	<b>734</b>	<b>1.84</b>	OMP	512	7	733	1.84	734	1.84	<b>734</b>	<b>1.84</b>
719.clvleaf_m	OMP	512	7	868	2.13	869	2.13	<b>869</b>	<b>2.13</b>	OMP	512	7	764	2.42	766	2.42	<b>766</b>	<b>2.42</b>
728.pot3d_m	OMP	512	7	1058	1.75	<b>1060</b>	<b>1.74</b>	1062	1.74	OMP	512	7	1048	1.77	1050	1.76	<b>1049</b>	<b>1.76</b>
734.hpgmgfv_m	OMP	512	7	490	2.04	496	2.02	<b>494</b>	<b>2.02</b>	OMP	512	7	490	2.04	496	2.02	<b>494</b>	<b>2.02</b>
735.weather_m	OMP	512	7	482	4.98	<b>483</b>	<b>4.97</b>	484	4.96	OMP	512	7	482	4.98	<b>483</b>	<b>4.97</b>	484	4.96

SPEChpc 2021\_med\_base = 2.53

SPEChpc 2021\_med\_peak = 2.58

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



# SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021\_med\_base = 2.53

SPEChpc 2021\_med\_peak = 2.58

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Jul-2023  
**Hardware Availability:** Jan-2023  
**Software Availability:** Apr-2023

### Hardware Summary

Type of System: Homogenous Cluster  
Compute Node: Intel Server D50DNP2MFALACB (Xeon 8480+)  
Interconnect: Mellanox HDR  
Compute Nodes Used: 32  
Total Chips: 64  
Total Cores: 3584  
Total Threads: 7168  
Total Memory: 16 TB  
Max. Peak Threads: 7

### Software Summary

Compiler: Intel oneAPI Compiler 2023.1.0  
MPI Library: Intel MPI Library 2021.9 for Linux OS  
Other MPI Info: None  
Other Software: None  
Base Parallel Model: OMP  
Base Ranks Run: 512  
Base Threads Run: 7  
Peak Parallel Models: OMP  
Minimum Peak Ranks: 512  
Maximum Peak Ranks: 512  
Max. Peak Threads: 7  
Min. Peak Threads: 7

### Node Description: Intel Server D50DNP2MFALACB (Xeon 8480+)

#### Hardware

Number of nodes: 32  
Uses of the node: Compute  
Vendor: Intel  
Model: Intel Server D50DNP2MFALACB (Xeon 8480+)  
CPU Name: Intel Xeon Platinum 8480+  
CPU(s) orderable: 1, 2 chips  
Chips enabled: 2  
Cores enabled: 112  
Cores per chip: 56  
Threads per core: 2  
CPU Characteristics: Turbo Boost Technology up to 3.8 GHz  
CPU MHz: 2000  
Primary Cache: 32 KB I + 48 KB D on chip per core  
Secondary Cache: 2 MB I+D on chip per core  
L3 Cache: 105 MB I+D on chip per chip  
Other Cache: None  
Memory: 512 GB (16 x 32 GB 2Rx8 PC5-4800B)  
Disk Subsystem: 1 x 1 TB NVMe U.2 2.5" SSD  
Other Hardware: None  
Accel Count: None  
Accel Model: None  
Accel Vendor: None  
Accel Type: None  
Accel Connection: None  
Accel ECC enabled: None  
Accel Description: None  
Adapter: Mellanox ConnectX-6 HDR  
Number of Adapters: 1  
Slot Type: PCI-Express 4.0 x16  
Data Rate: 200Gbit/s  
Ports Used: 1  
Interconnect Type: Mellanox HDR

#### Software

Accelerator Driver: None  
Adapter: Mellanox ConnectX-6 HDR  
Adapter Driver: 5.9-0.5.5  
Adapter Firmware: 20.36.1010  
Operating System: Rocky Linux 8.7 (Green Obsidian)  
4.18.0-372.32.1.el8\_6.crt3.x86\_64  
Local File System: NFS  
Shared File System: PANASAS FS  
System State: Multi-user  
Other Software: None



# SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc2021\_med\_base = 2.53

SPEChpc2021\_med\_peak = 2.58

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Jul-2023  
**Hardware Availability:** Jan-2023  
**Software Availability:** Apr-2023

## Interconnect Description: Mellanox HDR

### Hardware

### Software

Vendor: Mellanox  
Model: Mellanox HDR  
Switch Model: Mellanox MQM8790-HS2F Quantum HDR InfiniBand Switch  
Number of Switches: 18  
Number of Ports: 40  
Data Rate: 200 Gbit/s  
Firmware: 20.36.1010  
Topology: Fat-tree  
Primary Use: MPI Traffic

: --

## Submit Notes

The config file option 'submit' was used.

## General Notes

The PANASAS filesystem as described on this result page was formerly generally available. At the time of this publication, it may not be shipping, and/or may not be supported, and/or may fail to meet other tests of General Availability described in the SPEC HPG Policy document, <http://www.spec.org/hpg/policy.html>

## Compiler Version Notes

=====  
CC 705.lbm\_m(base, peak) 718.tealeaf\_m(base, peak) 734.hpgmgfv\_m(base, peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler 2023.1.0 (2023.1.0.20230320)  
Target: x86\_64-unknown-linux-gnu  
Thread model: posix  
InstalledDir:  
/global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm  
Configuration file:  
/global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm/./bin/icx.cfg  
=====

=====  
FC 719.clvleaf\_m(peak) 728.pot3d\_m(peak)  
=====

ifort (IFORT) 2021.9.0 20230302  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

(Continued on next page)



# SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc2021\_med\_base = 2.53

SPEChpc2021\_med\_peak = 2.58

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Jul-2023  
**Hardware Availability:** Jan-2023  
**Software Availability:** Apr-2023

## Compiler Version Notes (Continued)

=====  
FC 719.clvleaf\_m(base) 728.pot3d\_m(base) 735.weather\_m(base, peak)  
=====

ifx (IFX) 2023.1.0 20230320  
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.  
=====

## Base Compiler Invocation

C benchmarks:  
mpiicc -cc=icx

Fortran benchmarks:  
mpiifort -fc=ifx

## Base Portability Flags

705.lbm\_m: -lstdc++ -std=c++14  
718.tealeaf\_m: -lstdc++ -std=c++14  
734.hpgmgfv\_m: -lstdc++ -std=c++14

## Base Optimization Flags

C benchmarks:  
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto  
-funroll-loops

Fortran benchmarks:  
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512  
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto  
-funroll-loops -nostandard-realloc-lhs -align array64byte

## Base Other Flags

C benchmarks:  
-Wno-incompatible-function-pointer-types



# SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

**Intel**

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc2021\_med\_base = 2.53

SPEChpc2021\_med\_peak = 2.58

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Jul-2023  
**Hardware Availability:** Jan-2023  
**Software Availability:** Apr-2023

## Peak Compiler Invocation

C benchmarks:

mpiicc -cc=icx

Fortran benchmarks (except as noted below):

mpiifort

735.weather\_m: mpiifort -fc=ifx

## Peak Portability Flags

705.lbm\_m: -lstdc++ -std=c++14  
718.tealeaf\_m: -lstdc++ -std=c++14  
734.hpgmgfv\_m: -lstdc++ -std=c++14

## Peak Optimization Flags

C benchmarks:

705.lbm\_m: basepeak = yes  
718.tealeaf\_m: basepeak = yes  
734.hpgmgfv\_m: basepeak = yes

Fortran benchmarks:

719.clvleaf\_m: -O3 -Ofast -xCORE-AVX512 -ansi-alias -qopenmp -ipo  
-qopt-zmm-usage=high  
-qopt-multiple-gather-scatter-by-shuffles  
-nostandard-realloc-lhs -align array64byte  
728.pot3d\_m: Same as 719.clvleaf\_m  
735.weather\_m: basepeak = yes

## Peak Other Flags

C benchmarks:

-Wno-incompatible-function-pointer-types



# SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

## Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc2021\_med\_base = 2.53

SPEChpc2021\_med\_peak = 2.58

**hpc2021 License:** 13  
**Test Sponsor:** Intel  
**Tested by:** Intel

**Test Date:** Jul-2023  
**Hardware Availability:** Jan-2023  
**Software Availability:** Apr-2023

The flags file that was used to format this result can be browsed at  
[http://www.spec.org/hpc2021/flags/Intel\\_compiler\\_flags.2023-08-16.html](http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.html)

You can also download the XML flags source by saving the following link:  
[http://www.spec.org/hpc2021/flags/Intel\\_compiler\\_flags.2023-08-16.xml](http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.xml)

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEChpc2021 v1.1.7 on 2023-07-14 03:23:14-0400.  
Report generated on 2023-09-06 19:36:40 by hpc2021 PDF formatter v1.0.3.  
Originally published on 2023-09-06.